


ZWY-220/75L Crawler Mucking Loader

Item	Parameter
Model	ZWY-220/75L
Production capacity (m³/h)	220
Min turning radius (m)	≤10
Ground clearance (mm)	≥400
Digging width (mm)	≥6500
Unload distance (mm)	≥3400
Digging height (mm)	≥6000
Digging distance (mm)	≥3200
Unload height (mm)	≥2370
Digging depth (mm)	≥900
Grade ability (°)	≥18
Conveyor chain speed (m/min)	42
Ele-motor power (kw)	75
Tramming speed (m/s)	1.1±5%
Rated working pressure (MPa)	20
Check valve pressure (MPa)	21
Environ. temperature (°C)	-5 ~ +40
Empty weight (kg)	24500 (No liquid fill-in)
External dimensions (transport)	12700×2550×2500 (L×W×H)
Cooling method	Air-cooled/Water-cooled
Operate method	Hydr. Ctrl.



9	ZWY-220/75L-09	Cable reel	1	Assembly			
8	ZWY-220/75L-08	Diesel engine	1	Assembly			
7	ZWY-220/75L-07	Hydr. system	1	Assembly			
6	ZWY-220/75L-06	Electric system	1	Assembly			
5	ZWY-220/75L-05	Tramming system	1	Assembly			
4	ZWY-220/75L-04	Body	1	Assembly			
3	ZWY-220/75L-03	Conveyor	1	Assembly			
2	ZWY-220/75L-02	Cab	1	Assembly			
1	ZWY-220/75L-01	Gathering system	1	Assembly			

S/N	Code	Name	Qty	Material	Unit	Total Weight	Remark
General Drawings							KAMACH
Mark	Part	Rev.	Signature	Date	ZWY-220/75L MUCKING LOADER		
Designed by	Standard				Scheme	Weight	Scaler
Checked by	Approved by				1-20 ZWY-220/75L.00		
Process	Date				Total page	Page	